

STA-STUCK - SPECIAL SPRAY ADHESIVE - For bonding acoustic foam

Key Benefits



- Ideal to stick most of our sound absorber products
- Water and heat resistant.
- Varying web spray nozzle
- Low solvent content
- Heat resistant up to 250°F/121°C
- Supplied in a can of 15oz (500ml) Spray Coverage: 6-8m²/can

Description

Our Sprayable Contact Adhesive is a contact adhesive ideal for sticking acoustic foam to a wide variety of surfaces with no adverse effect. It has a high solids content and is water resistant and heat resistant with permanent flexibility.

Directions

Shake can well before use (especially in cold conditions) Best results are obtained when working in an ambient temperature of 70°F/21°C with surfaces to be bonded properly conditioned. Ensure all surfaces are thoroughly clean and free from moisture, dirt, dust and grease or any other materials that could affect the bond. For vertical or horizontal patterns, turn tip in spray nozzle clockwise to adjust the spray pattern. Hold spray can 6 to 8 inches from the surface and apply in even coats, making sure the adhesive 'webs' across the surface. Do not hold closer than 6 inches or 'wet' the surface.



It is important the adhesive 'webs' across the surface and 80-100% coverage is achieved. One surface should be sprayed vertically and the other horizontally. Do not concentrate in one spot or allow the adhesive to 'puddle'. Double coated applications are recommended on porous surfaces (after the first coat has dried, apply a second coat evenly on top). Allow adhesive to tack (approx 2-4 minutes) and bond together with a firm pressure over the entire area. Tack time can vary depending on climate conditions. It is important that maximum uniform pressure is applied to over the entire area bonded to achieve maximum bond strength. Use the Spray Contact Adhesive in well ventilated conditions.

ADDITIONAL INFORMATION AND INSTALLATION DETAIL CAN BE FOUND ON OUR WEBSITE